





























# ACCZENT EXCELLENCE 70 SILVER




Silver - Metal Blue



 White Gold	 Silver Grey	 Gold	 Metal Blue
 5722 001  5327 001  5710 001	 5722 002  5327 002  5710 002	 5722 003  5327 003  5710 003	 5722 004  5327 004  5710 004
 Grey Blue	 Beige	 Light Grey	
 5722 005  5327 005  5710 005	 5722 006  5327 006  5710 006	 5722 007  5327 007  5710 007	

TECHNICAL DATA	STANDARDS	Accent Excellence 70 Silver
<b>Classification</b>		
Classification	ISO 10874 (EN 685) commercial industrial	Classes: 34 43
<b>Characteristics</b>		
Total thickness	ISO 24346 (EN 428)	2.00mm
Wear layer thickness	ISO 24340 (EN430)	0.70mm
Total weight	ISO 23997 (EN 430)	2 360g/m <sup>2</sup>
PU treatment	-	TopClean
Abrasion group	EN 660-2	Group T: ≤ 2mm <sup>3</sup>
<b>Technical performances</b>		
Residual indentation	Average measured value	≤ 0.10mm
	ISO 24343-1 (EN 433) requirement	
Reaction to fire	EN 13501-1	B <sub>1</sub> S1 glued over any A2 <sub>1</sub> or A1 <sub>1</sub> substrate (concrete) and over any derivative wood substrate
Slip resistance	DIN 51130 EN 13893	R10 μ ≥ 0.30
Dimensional stability	ISO 23999 (EN 434)	≤ 0.10%
Furniture leg	EN 424	No damage
Castor wheel test	ISO 4918 (EN 425)	No damage
Curl resultant to heat	ISO 23999 (EN 434)	≤ 8mm
Electrostatic properties	EN 1815 EN 1081	≤ 2kV on concrete R1 > 10 <sup>9</sup> ohms
Chemical resistance	ISO 26987 (EN 423)	High resistance
Hygiene	-	Does not contribute to infection spreading
Thermal resistance Underfloor heating	EN ISO 10456	0.02m <sup>2</sup> K/W Suitable
Light fastness	EN ISO 105-B02	≥ 6
Impact sound reduction	Standards EN ISO 10140-8 EN ISO 717/2	10dB

The above information is subject to modifications for the benefit of further improvement (01/2014). For more detailed technical information, please contact Tarkett.



Beige Red  
5722 008  
5327 008  
5710 008

# ACCZENT EXCELLENCE 70 SILVER

## Main Product Features

- Comfort and a safety touch
- Comfortable floor with 10dB acoustic
- Superior anti slip resistance (R10)
- Available in 2, 3 and 4 meter widths
- Inlaid designs

## Surface Treatment



## Sustainability Tag



(1) Progressively for all our professional vinyl products during 2014

## Logistics Information



Available in rolls:  
2m, 3m & 4m  
Rolls length: 251m

## Laying direction:



## General Information



According to European Classification ISO 10874 (EN 685)



Play with the Room Designer